

MOBILELEASE

Equipment and vehicle leasing since 1980

2020 Chevrolet Silverado 4500 HD \$33,500

Dealer Information

To get more details or set up a test drive this vehicle

Call us now:(713) 683-9500 3815 Dacoma St. Houston, Texas 77092



- Stock #:R-8152
- VIN:54DCDW1B3LS801286
- Mileage:42116
- Location:Houston, Texas 77092
- Body Style:Truck
- Int.Color:Gray
- Ext.Color:White
- Transmission:Automatic
- Engine:8 Cylinder Engine

Dealer Comments

Get it while it's hot! 8 Cylinder Engine, 6-Speed A/T, Rear Wheel Drive, and . You'll love the added privacy you'll get with this 2020 4500 Lcf Gas's tinted windows.

Installed Features

- Brake
- parking
- cable actuated
- internal expanding drum type
- transmission-mounted|Daytime Running Lamps|Assist steps|Glass
- tinted|Mirror
- outside left hand and right hand dual cab mounted exterior with integral convex mirror|Tires
- front
- 225/70R19.5 G 128/126 L BW HWY VAR1|Tires
- rear
- 225/70R19.5 G 128/126 L BW HWY VAR1|Wheels
- 19.5 x 6

- K steel|Windshield wiper
- pulse
- wet arm|Air conditioning
- single-zone manual
- integral in-dash mounted|Cup holders|Driver Information Center|Floor mats|Lighting
- interior dome|Steering column
- Tilt-Wheel|Steering wheel
- urethane|Storage
- door pockets|Storage
- seatback pockets|Windows
- power|Windshield washer bottle access on passenger side dash when passenger-side door is open|Air cleaner
- heavy-duty
- 11 diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.|Alternator
- 145 amps output with integral regulator|Axle
- 4.30 ratio (Standard on 4500 model only.)|Battery
- 750 cold-cranking amps
- 12-volt single
- maintenance free
- frame-mounted battery box|Brakes
- 4-wheel antilock
- front disc
- rear drum
- dual circuit
- vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical
- transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system.|Exhaust
- single outlet|Frame
- ladder-type channel frame. Full C section straight frame 33.5 (85.1 cm) wide. Yield strength 44
- 000 psi
- section modulus 7.20 cu.in. and RBM 316
- 800 lb-ft/in per rail.|Front axle
- 6
- 830 lbs. (3098 kg)
- reverse Elliot I-beam includes integral hydraulic power steering. ratio 18.8-20.9:1|Front suspension
- 8
- 440 lbs. (3828 kg) tapered leaf
- semi-elliptical steel alloy tapered leaf springs. Includes shock absorbers and stabilizer bar.|Fuel tank
- 38.6 Gallon
- (146L)
- rectangular fuel tank. mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill. (Not available with (L96) Vortec 6.0L V8 SFI engine.)|GVWR
- 14
- 500 lbs. (6577 kg)|Incomplete vehicle certification|Rear axle
- 11
- 020 lbs. (4998 kg) R050
- full-floating single-speed with oil lubricated rear wheel-bearings|Rear suspension
- 12
- 900 lbs. (5851 kg)
- multi-leaf
- semi-elliptical steel alloy. Includes shock absorbers|Vehicle Application Truck|Wheelbase
- 150 (381.0 cm)|Audio system feature
- 2 speakers|ENGINE
- VORTEC 6.0L V8 SFI
- GMPT-V8 8 CYLINDER V BLOCK
- FOUR CYCLE OVERHEAD VALVE WATER COOLED|

Sales Tax, License Fee, Registration Fee, Dealer Documentary Fee, Finance Charges, Emission Testing Fees and Compliance Fees are additional to the advertised price.